

Epoxy RFID NFC Mini Tag

Feature

- Robust Waterproof, Dustproof for industrial environment
- Flexible RFID protocol, Frequencies with adjustable performance
- Customized code printing and encoding
- Easily integrated for industrial Identification applications



Application

- Product Authentication
- Tools / Instruments Locator
- Asset Management
- Miniature Tag Applications

Specification

Frequency:	13.56MHz
Protocol:	ISO14443A / ISO15693 / ISO18092
Chip:	NXP MIFARE Classic® / ICODE SLIX / NTAG213
Size:	Dia.15mm / 18mm; Thickness: 2.8~3mm
Reading Range	10~50mm
Material:	PPS housing + Epoxy
Color:	Black or customized
Product Weight	Appr 1.5g
IP Class	IP67
Operating Temperature:	-10 ~ 60°C
Storage Temperature:	-25 ~ 85°C
Additional Craft for Optional	
Coding:	Chip encoding
On Metal:	Anti-Metal Layer optional, Thickness from 0.3~0.5mm
Adhesive:	Ordinary Adhesive sticker, 3M Adhesive Layer Optional
Warranty	1 year



The information contained on this Document is considered to be confidential material proprietary to HUAYUAN, and this information shall not be disclosed, duplicated or copied for any purpose, Nor made available for any third party without the prior consent to HUAYUAN

SHANGHAI HUAYUAN ELECTRONIC CO., LTD | 517, B-Bld, No. 399 Hengnan Rd, Shanghai 201112, China.
 T:+86 21 5424 6151 ; F: +86 21 5424 6163, info@huayuansh.com, www.huayuansh.com