

PCB FR4 On Metal UHF Gen2 Tag

Key Features:

- Smooth surface, Hard structure
- Good performance with directly attached on metal
- Firmly structure
- High temperature resistance and waterproof
- Wide adaptability for metal, especially in rugged environment

Application:

- Industrial Inventory Management
- Property Tracking
- Item Identification
- Patrol System
- Forklift, Trunk, Vehicle Management
- Street Light, Traffic Light and other Public Management



Tag Universal Specification:

| Tag officers of specification. | | | | | |
|--------------------------------|--|--|--|--|--|
| Frequency Range: | FCC, ETSI (HFR-9525) | | | | |
| Protocol: | EPC Class 1 Gen2 | | | | |
| Material: | FR-4, PCB, Double Side Copper Etching Antenna | | | | |
| IP Rating: | IP67 | | | | |
| Printing & Data: | Silk screen printing, Text printing with laser engraving, Spray paint Variable data process. | | | | |
| Installation: | Screw Fixing, Adhesive | | | | |
| Operating / Storage Temp.: | -40 ~ 150°C | | | | |

Variety of FR4 RFID On Metal Tag Spec for Optional:

| Item | HFR-3613 | HFR-4436 | HFR-5313 | HFR-8015 | HFR-8020 | HFR-9011 | HFR-9525 | HFR-10717 |
|----------------------|---------------|-------------|---------------|---------------|---------------|---------------|---------------|----------------|
| | ULK-2012 | HFK-4430 | ULK-2212 | HLK-9012 | HFK-6020 | HLK-3011 | HFN-9323 | HFK-10/1/ |
| Dimension (in mm) | 36 x 13 x 2.8 | 44 x 36 x 2 | 53 x 13 x 2.8 | 80 x 15 x 3.3 | 80 x 20 x 3.3 | 90 x 11 x 3.7 | 95 x 25 x 3.7 | 107 x 17 x 3.3 |
| Weight | 2.7g | 6g | 4g | 9g | 10.25g | 7.1g | 17.1g | 16.03g |
| Handheld | Up to 1M | Up to 3M | Up to 1M | Up to 3M | Up to 4M | Up to 4M | Up to 5M | Up to 3M |
| Fixed Reader | Up to 2M | Up to 6M | Up to 2M | Up to 6M | Up to 8M | Up to 8M | Up to 9M | Up to 6M |



-- 1 / 1--