

Plastic Housing RFID On Metal Tag

High performance in variety of industrial and logistical applications.
designed for difficult case contents such as metals.

Application:









- Perfect solution for automatic identification
- The asset and machinery maintenance
- Monitoring of production steps
- Tracking of container and bins for industrial purposes



Specification:

Frequency Range:	FCC, ETSI
Protocol:	EPC Class 1 Gen2
Printing & Data:	Silk screen printing or laser engraving. Variable data process: UID or serial number printing.
Installation:	Screw Fixing, Adhesive
Operating Temperature:	-40 ~ 85°C
Storage Temperature:	-40 ~ 104°C

Variety of On Metal Tag Spec for Optional:

Picture	Item No.	Dimension(mm)	Weight	Encasement	Reading Range
	HPM-4234	42 × 34 × 7	26g	Nylon	Up to 4m
	HPM-8520	85 × 20 × 11	11g	ABS	Up to 6m
	HPM-9824	98 × 24 × 12	32g	ABS, PC	Up to 6m
	HPM-10432	104 × 32 × 8.3	32g	PC	Up to 5m
	HPM-11833	118 × 33 × 12.1	32g	ABS	Up to 6m
	HPM-11832	118 × 32 × 6.2	32g	ABS	Up to 6m
	HPM-13221	132 × 21 × 13.5	17g	ABS	Up to 6m
	HPM-5858	58 × 58 × 4.0	10g	ABS	Up to 6m