

Worm RFID Waste Bin Tag

Feature

- Easily to be screwed onto the specific area of the waste bin.
- With its robust housing, it could withstand the harsh environment under the daily operation.
- Withstands Exposure to: Fuel B, Mineral oil, Petroleum, Salt mist, Vegetable oil.



Specification

Frequency Range:	125kHz, 134.2kHz / 13.56MHz / 860~960MHz
Dimension:	Dia.30*15mm; Hole diameter: 5.5mm
Reading Range:	LF: 5~10cm / HF: 5cm / UHF: 2m ~ 3m
Material:	Nylon + Epoxy filling
Weight	9.6g
IP Rating:	IP67, 20°C, 1m x 1h
Axial/Radial Force:	1000 N, 10 sec
Shock:	IEC 68.2.29(40G, 18ms, 6 axis, 2000 times)
Operating Temperature:	-25 ~ 120°C
Storage Temperature:	-40 ~ 200°C
Coding:	Variable data process
Custom Logo:	Custom Laser Engrave

Application

- Waste Management



The information contained on this Document is considered to be confidential material proprietary to HUAYUAN, and this information shall not be disclosed, duplicated or copied for any purpose, Nor made available for any third party without the prior consent to HUAYUAN

SHANGHAI HUAYUAN ELECTRONIC CO., LTD | 517, B-Bld, No. 399 Hengnan Rd, Shanghai 201112, China.

T:+86 21 5424 6151 ; F: +86 21 5424 6163, info@huayuansh.com, www.huayuansh.com