


HN1431I

HF RFID Inlay



Features

- * Ideal RFID for small item level packages applications, like wristbands
- * Small dimension, steady performance and no reading blind spot
- * Both horizontal and vertical versions are available

Specification

Antenna Dimension	14x31mm
Inlay/Tag Dimension	17x34mm
Chip	ICODE SLIX, ICODE SLIX2
Frequency	13.56MHz
Memory	1024 bits, 1024 bits, 2560 bits
Base Material	PET
Protocol	ISO15693
Life time	10 years
Operating Mode	Passive
Read Ranger	Up to 1.5m

Environment & Package


Operating Temperature	-40°C to +85°C
Storage Temperature	-40°C to +85°C
Package	5000 pcs/roll, 4 rolls/carton

Delivery Formats

Available Formats	Dry Inlay, Wet Inlay, RFID Tag
Quality	100% tested with out-of-tolerance inlay marked
Inner Core Diameter	76 mm/3 inch

Package Info.:

ESD package box 5,000pcs/roll, 4 or 8 rolls/ctn. Packing in roll for printing and cutting at customer



The information contained on this Document is considered to be confidential material proprietary to HUAYUAN, and this information shall not be disclosed, duplicated or copied for any purpose, Nor made available for any third party without the prior consent to HUAYUAN.----- 1 / 1

